



A-B NON REPAIRABLE AREA		
7.00-8.75	3"	75 mm
9.00-14.00	4"	100 mm
16.00-18.00	5"	125 mm
21.00-27.00	6"	150 mm

NON-REPAIRABLE AREA - TRACTOR		
14.9-20.8	4"	100 mm
23.1 and above	5"	125 mm

Bias ply tyre Repair Chart

SIZE OF INJURY



PLY RATING	Inch	1/8"	1/4"	3/8"	1/2"	3/4"	1"	1 1/2"	2"	2 1/2"	3"	4"	4 1/2"	5"
	mm	3	6	10	13	20	25	40	50	65	75	100	115	125
4	CBP 0	CBP 0	CBP 1	CBP 2	CBP 3	CBP 3	CBP 4	CBP 5						
6-8	CBP 0	CBP 1	CBP 2	CBP 3	CBP 3	CBP 4	CBP 4	CBP 5						
10-12	CBP 0	CBP 1	CBP 2	CBP 3	CBP 4	CBP 4	CBP 5	CBP 6	CBP 6	CBP 7	CBP 8			
14-16	CBP 0	CBP 1	CBP 3	CBP 4	CBP 4	CBP 5	CBP 6	CBP 6	CBP 7	CBP 7	CBP 8	CBP 8	CBP 9	CBP 10
18-20	CBP 0	CBP 1	CBP 4	CBP 4	CBP 5	CBP 6	CBP 6	CBP 7	CBP 8	CBP 8	CBP 9	CBP 9	CBP 10	CBP 10
20-22	CBP 0	CBP 1	CBP 4	CBP 5	CBP 6	CBP 7	CBP 8	CBP 8	CBP 9	CBP 9	CBP 9	CBP 9	CBP 10	

This chart is a guideline only. Consult tyre manufacturer for repair limitations.
For sidewall repairs use CSP series patches instead of CBP series patches.

For ply damages upto half of the carcass thickness on Tread, Shoulder, Sidewall

SIZE OF INJURY



PLY RATING	Inch	1/8"	3/8"	1/2"	1"	2"	3"	4"	5"
	mm	3	10	13	25	50	75	100	125
8-12	CBP 0	CBP 1	CBP 2	CBP 3	CBP 4	CBP 6	CBP 7	CBP 8	
14-18	CBP 0	CBP 1	CBP 2	CBP 4	CBP 5	CBP 6	CBP 7	CBP 8	
20-22	CBP 0	CBP 2	CBP 3	CBP 5	CBP 6	CBP 7	CBP 8	CBP 9	

This chart is a guideline only. Consult tyre manufacturer for repair limitations.
For sidewall repairs use CSP series patches instead of CBP series patches.

Tractor Tyre Repair Chart

SIZE OF INJURY



PLY RATING	Inch	2"	3"	4"	5"	6"	7"
	mm	50	75	100	125	150	175
4 - 6	CBP 5	CTP 1	CTP 1	CTP 2	CTP 2	CTP 3	
8 - 12	CTP 4	CTP 4	CTP 4	CTP 5	CTP 5	CTP 6	
14 - 16	CTP 4	CTP 5	CTP 5	CTP 6	CTP 6	CTP 7	

This chart is a guideline only. Consult tyre manufacturer for repair limitations.