


## Passenger Tyre Repair Chart



CROWN INJURY Inches (mm)	SIDEWALL INJURY		Passenger	Tyre Sizes
	Width Inches(mm)	Length Inches(mm)		
¼" (6mm)	¼" (6mm)	½" (13mm)	10	10
	¼" (6mm)	1½" (40mm)	12	12
⅜" (10mm)	¼" (6mm)	2" (50mm)	14	14
	⅜" (10mm)	⅜" (10mm)	10	10
½" (13mm)	⅜" (10mm)	1½" (40mm)	12	12
	⅜" (10mm)	2" (50mm)	14	14
¾" (20mm)	½" (13mm)	1½" (40mm)	12	12
	½" (13mm)	2" (50mm)	14	14
1" (25mm)	¾" (20mm)	1½" (40mm)	12	14
	¾" (20mm)	2" (50mm)	14	14
1" (25mm)	1" (25mm)	1½" (40mm)	14	14
	1" (25mm)	2" (50mm)	14	22



C - CROWN INJURY  
W - WIDTH OF INJURY  
L - LENGTH OF INJURY  
T-S - SHOULDER AREA  
T-T - CROWN AREA  
A-B - NON REPAIRABLE AREA

### NON-REPAIRABLE AREA

Passenger	1½" (40 mm)
6.50 -7.00	2½" (65 mm)
7.50 -16.00	3" (75 mm)

## Truck Radial Tyre Repair Chart



CROWN INJURY Inches (mm)	SIDEWALL INJURY		Use Radial repair patch number - CRP Truck Tyre Size		
	Width Inches (mm)	Length Inches (mm)	6.00 -7.50 7R - 8.5R 215/- 235/-	8.25 - 10.00 9R -11R 235/- 285/-	11.00 -14.00 12R -16.5R 295/- 425/-
(3mm)	⅛" (3mm)	⅛" (3mm)	10	10	10
¼" (6mm)	⅜" (10mm)	⅜" (10mm)	12	12	12
	1 Cable	1½" (40mm)	20	20	20
⅜" (10mm)	1 Cable	3" (75mm)	22	22	22
	1 Cable	5" (125mm)		24	24
½" (13mm)	1 Cable	6" (150mm)		26	26
			22	33	33
½" (13mm)	2 Cable	¾" (20mm)	20	20	22
	2 Cable	1½" (40mm)	20	22	24
½" (13mm)	2 Cable	2½" (65mm)	22	24	26
	2 Cable	5 ½" (130mm)		26	26
¾" (20mm)	⅜" (10mm)	1½" (40mm)	20	26	40
	⅜" (10mm)	2 ⅜" (60mm)	22	26	40
¾" (20mm)	⅜" (10mm)	3 ⅜" (80mm)	26	26	42
	⅜" (10mm)	5" (125mm)		26	42
¾" (20mm)			24	33	35
	½" (13mm)	1½" (40mm)	22	40	40
¾" (20mm)	½" (13mm)	2½" (65mm)	22	40	42
	½" (13mm)	4" (100mm)		42	44
¾" (20mm)	½" (13mm)	5" (125mm)		42	44
	¾" (20mm)	1" (25mm)	22	40	42
¾" (20mm)	¾" (20mm)	2½" (65mm)		42	44
	¾" (20mm)	4 ⅛" (110 mm)		42	44
1" (25mm)	¾" (20mm)	5 ½" (130mm)		44	44
			33	35	35
1" (25mm)	1" (25mm)	2" (50mm)	40	42	44
	1" (25mm)	3" (75mm)		42	44
1¼" (32mm)	1" (25mm)	4" (100mm)		44	44
				37	37
1¼" (32mm)	1¼" (32mm)	2" (50mm)		42	44
	1¼" (32mm)	3 ⅜" (80mm)		44	44
1½" (40mm)	1¼" (32mm)	4" (100mm)		44	44
				37	37
1½" (40mm)	1½" (40mm)	2" (50mm)		44	44
	1½" (40mm)	3 ⅜" (80mm)		44	44
1½" (40mm)	1½" (40mm)	4" (100mm)		44	46


Radial Repair patches CRP 33, 35, 37 are specially meant for crown injury repairs.

This chart is a guideline only. Consult tyre manufacturer for repair limitations.

## Tractor Tyre Repair Chart



CROWN INJURY Inches (mm)	SIDEWALL INJURY		Tractor Tyre Sizes	
	Width Inches(mm)	Length Inches(mm)	8 - 11 8.3-12.4	12 - 15 13.6-30.5
3/8" (10mm)	3/8" (10 mm)	3/8" (10mm)	12	12
3/4" (20mm)	3/8" (10 mm)	1 1/2" (40mm)	20	20
	3/4" (20 mm)	2" (50mm)	22	80
1 1/2" (40mm)	1 1/2" (40 mm)	3" (75mm)	80	82
	2" (50 mm)	2" (50mm)	80	82
2 1/2" (65mm)	2 1/2" (65 mm)	4" (100mm)	82	82
3 1/2" (90mm)	3" (75 mm)	3" (75mm)	82	82
	3" (75 mm)	5" (125mm)	82	82
5" (125mm)	3" (75 mm)	4" (100mm)		84
	4" (100 mm)	6" (150mm)		86
	5" (125 mm)	5" (125mm)		86



**A-B NON-REPAIRABLE AREA**

14.00 - 16.00 (15.5 - 17.5)	3"	75mm
18.00 - 24.00 (20.5 - 29.5)	5"	125mm
27.00 - 33.00 (33.25 - 37.5)	6"	150mm
40/65 - 50/65 (40.5)	6 3/4"	170mm
36.00	8"	200mm
37.00 - 40.00 (50.5 & larger)	10"	255mm

## OTR (Off The Road) Radial Repair Chart



CROWN INJURY Inches (mm)	SIDEWALL INJURY		SHOULDER INJURY Inches (mm)	Earthmover Tyre Sizes		
	Width Inches (mm)	Length Inches (mm)		14.00 - 16.00 15.5 - 17.5 20/65 - 25/65	18.00 - 30.00 20.5 - 37.5 35/65 - 45/65	33.00 - 40.00 37.5 - 50.5 50/65 - 65/65
3/4" (20mm)				45	45	45
1" (25mm)				45	45	45
1 1/2" (40mm)				45	55	55
2" (50mm)				55	55	65
2 1/2" (65mm)				55	65	65
3 1/2" (90mm)					75	75
5" (125mm)					75	75
			3/4" (20mm)	46	50	52
			1" (25mm)	46	52	52
			1 1/2" (40mm)	50	52	56
			2" (50mm)	50	56	56
			2 1/2" (65mm)	56	72	72
			3" (75mm)		72	72
	3/4" (20mm)	3" (75mm)		44	44	50
	3/4" (20mm)	6" (150mm)		46	46	50
	3/4" (20mm)	8" (200mm)		46	50	50
	1" (25mm)	6" (150mm)		46	46	50
	1" (25mm)	10" (250mm)		50	52	56
	2" (50mm)	6" (150mm)		50	50	52
	2" (50mm)	10" (250mm)		52	52	56
	2" (50mm)	12" (300mm)			56	60
	2" (50mm)	16" (400mm)			60	60
	3" (75mm)	8" (200mm)			56	56
	3" (75mm)	10" (250mm)		52	56	72
	3" (75mm)	12" (300mm)			56	60
	4" (100mm)	6" (150mm)			56	56
	4" (100mm)	8" (200mm)		52	72	72
	4" (100mm)	10" (250mm)			60	60

Radial Repair patches CRP 45,55,65,75 are specially meant for crown injury repairs.

This chart is a guideline only. Consult tyre manufacturer for repair limitations.